

TL600™

gen2 active PA system

CHARACTERISTICS

- Three-way active column speaker PA system
- TWS function
- Connections: Bluetooth; XLR; RCA
- Variable frequency crossover
- RCA and XLR derivations, high pass and full range
- Color digital display
- DSP control knob
- Power and clipping indicator LEDs
- Voltage selector 110/220 V
- Subwoofer phase inversion
- Buttons: mode, volume +/-, track +/-, repeat, play/pause, TWS, and back for navigation and control
- Independent volumes for subwoofer and satellite
- Includes:
 - Power cable
 - Mid-high satellite
 - Subwoofer
 - Variable height stand with built-in connector



TL600 gen2

TL600™

gen2 active PA system

SPECIFICATIONS

- Color: Black
- Connectivity: Bluetooth; RCA; XLR
- Frequency response: 25 – 20 kHz
- Power output: 600 W RMS
- Distortion: < 1%
- Signal-noise ratio (S/R) > 85 dB
- Drivers:
 - High: 1" (x1); 8 Ω; silk
 - Mid: 3" (x4); 4 Ω
 - Low: 10" (x1); 4 Ω; magnetic isolation
- Materials: subwoofer wooden box with bass reflex / satellite tower wooden box with iron mesh
- Bluetooth range: 10 m
- Bluetooth version: 5.4
- Bluetooth Audio Codec: AAC
- Power cable length: 1,5 m
- Variable crossover: 40 – 160 Hz

LOGISTICS

- Master Carton (and Gift Box): 460 x 390 x 630 mm - 26,5 kg
- EAN: 4260411276333
- DUN: 14260411276330
- HK: HK096-03672-2



TL600 gen2