

# TP15™

gen2 active pa

## CHARACTERISTICS

- Two-way active PA system
- TWS connection
- Bass Reflex
- Color digital display
- LED illuminated logo
- Signal and clipping indicator LEDs
- Ø 35 mm stand anchorage (2 positions)
- 3 independent input channels
- XLR full range output derivation
- Mic/Line input selector (inputs 1 and 2)
- Independent input volume controls
- Connections: Bluetooth; XLR/TRS (x2); RCA; AUX 3,5 mm
- DSP with 4 preset equalizations
- 32-Bit DSP with multiband equalization, treble and bass control, echo, delay and reverb
- Variable crossover for low frequency, ideal to match with external subwoofer
- Voltage selector 110/220 V
- Buttons: mode, vol +/-, previous, next, play/pause for navigation and control
- Support 3 different positions (Totally horizontal, totally vertical, horizontal with inclination as floor monitor)
- Includes power cable

GEN2  
TP15

# TP15™

gen2 active pa

## SPECIFICATIONS

- Color: Black
- Bluetooth range: 10 m
- Bluetooth version: 5.4
- Bluetooth Audio Codec: AAC
- Frequency response: 20 – 20k Hz
- Power output: 450 W RMS
- Distortion < 0,5%
- Signal-noise ratio (S/N) > 90 dB
- Drivers:
  - High frequency: 1,75" (x1); 8 Ω; Titanium
  - Low frequency: 15" (x1); 4 Ω; magnetic isolation
- Product size: 420 x 420 x 710 mm
- Materials: iron mesh / PP plastic box
- Connectivity: Bluetooth; XLR/TRS (x2); RCA; Aux 3,5mm
- Power cable length: 2 m

## LOGISTICS

- Master Carton (and Gift Box): 465 x 465 x 765 mm; 24,5 kg
- EAN: 4260411276838
- DUN: 14260411276835
- HK: HK096-03671-2

2  
N  
E  
G  
S  
1  
P  
T

